



特性: Specifications:

电器: Electrical:

1. 接触阻抗: Contact Resistance
30 milliohms MAX
2. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
3. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

机构: Mechanical:

1. 结合力: Mating Force:
4.0KG MAX 最大4kg
2. 拔出力: Unmating Force:
0.7 KG MIN 最少0.7kg

材料: Material:

1. 塑胶: Housing: High Temperature Thermoplastic
UL 94V-0 耐高温塑胶
2. 端子: Contact: Copper Alloy 铜合金
3. 铁壳: Shell: Copper Alloy 铜合金

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
接触点镀金, 脚镀锡

2. 铁壳: Shell:

Nickel Plating 镀镍

深圳市志杰威科技有限公司



| | | | | | |
|----|------------------------------|------|--|----|------------|
| 品名 | USB A TYPE 无后盖 90度 SMT 母座 | 材质 | | 单位 | MM |
| 图号 | CP-UB001-2A | 图纸编号 | | 比例 | 1:1 |
| 制图 | | 审核 | | 日期 | 2007.05.18 |