

Interface.....Centronics Parallel
(IBM Port)

Print Method.....Impact Dot Matrix (Logic Seeking)

Print Head.....24 Pins

Emulation.....IBM Proprinter XL24E
Epson LQ-1050

Buffer Size.....32K Buffer
32K Download
equals 64K Max

Power Supply.....100V AC ± 10%, 50/60Hz
120V AC ± 10%, 60Hz
220V AC ± 10%, 50Hz
240V AC ± 10%, 50Hz

Power Consumption:
Printing.....40 W (typ.), 120 W (max.)
Standby.....9 W

Weight.....19.87 lbs

Dimensions.....4.5 (H) x 22.5 (W) x 12.4 (D) inches

Environmental Conditions:
Operating Temperature.....55 to 80°F (13 to 30°C)
Humidity.....20 to 80% RH, non-condensing
Storage Temperature.....-40 to 150°F (-40 to 66°C)
Humidity.....10 to 90% RH, non-condensing

Paper Feed Method.....Friction feed, Tractor feed

Paper:
Types of Paper.....Fanfold, Single Sheets
Width.....101.6-381 mm (4-15")
Thickness.....0.06-0.28 mm (0.0024 - 0.011")
No. of Copies.....Original + three copies (Total thickness must be
less than the maximum thickness value given above)

Line Feed Directions.....Forward
Reverse

Line Feed Increments.....1/6", 1/8", n/60", n/180", n/360"

Line Feed Speed.....MAX. 3 IPS

Print Speed:
Draft Mode
10 cpi.....200 cps
12 cpi.....240 cps
15 cpi.....300 cps
17.1 cpi.....171 cps
20 cpi.....200 cps
LQ Mode
10 cpi.....83 cps
12 cpi.....100 cps
15 cpi.....125 cps

17.1 cpi.....142 cps
20 cpi.....166 cps

Character Types.....ASCII Characters
International Characters
Block Characters
Line Drawing Characters

Print Format:

Draft Mode

10 cpi.....18(V) x 12(H)
12 cpi.....18(V) x 12(H)
15 cpi.....16(V) x 8(H)
17.1 cpi.....18(V) x 12(H)
20 cpi.....18(V) x 12(H)

LQ Mode

10 cpi.....20(V) x 36(H)
12 cpi.....20(V) x 30(H)
15 cpi.....16(V) x 24(H)
17.1 cpi.....20(V) x 21(H)
20 cpi.....20(V) x 18(H)
Proportional.....20(V) x n(H)

Character Pitch:

Pica.....10 cpi, 136 columns
Elongated Pica.....5 cpi, 68 columns
Elite.....12 cpi, 163 columns
Elongated Elite.....6 cpi, 81 columns
Condensed.....17.1 cpi, 233 columns
Elongated Condensed.....8.55 cpi, 116 columns
Condensed Elite.....20 cpi, 272 columns

Ribbon:

Standard Black Ribbon Cassette (26-2869)