

OPERATING FREQUENCIES

Channel	Base Transmit	Base Receive	Remote Keypad Transmit	Remote Keypad Receive
I	46.710 MHz	49.770 MHz	49.770 MHz	46.710 MHz
M	46.870 MHz	49.930 MHz	49.930 MHz	46.870 MHz
N	46.930 MHz	49.990 MHz	49.990 MHz	46.930 MHz
O	46.970 MHz	49.970 MHz	49.970 MHz	46.970 MHz

GENERAL

Transmit RF Output.....9800 microV/m
 Pulse Mode Dialing Rate.....10 pps
 Pause Entry Delay.....2 Seconds
 Interdigital Pause.....850 mS
 Redial Memory Capacity.....16 Digits
 Power Requirements
 Base.....120 Volts AC
 Handset.....3.6 Volts DC (Nickel-Cadmium Battery)
 Weight.....1.6 lb.
 Measurements
 Base.....3 x 5 x 1 1/4 x Inches
 Handset.....4 3/4 x 5 x 5 1/2 Inches

OPERATING PARAMETERS

We provide this information to help you answer questions your phone company might ask.

Interface.....Loop Start
 Connector.....USOC Type RJ11C
 Ringer.....Standard Bridged Ringer
 20-60 Hz Sine or Square Wave, 40-130 Volts Ring Signal
 Resistance.....100M Ohm (On Hook), 300 Ohm (Off Hook)

(SMM/all-06/06/94)